

MTMA/CONNECT

INTERCOM MODULE FOR 4G LTE SYSTEMS

COMPATIBLE SYSTEMS

4G



TECHNICAL DATA

IP protection rating	54
Operating temperature (°C)	-25 ÷ +55
Storage temperature (°C)	-25 ÷ +70
Current draw (mA)	180
Current draw in standby mode (mA)	65
Power supply (V DC)	14 - 24 AC/DC
GSM transmission power - 900 MHz (dBm)	33 dBm
GSM DCS transmission power - 1800 MHz (dBm)	30 dBm
LTE transmission power (dBm)	23
LTE frequency bands	B1/B3/B7/B8/ B20

The module can make audio calls in speaker mode to telephone numbers on fixed and mobile networks by pressing call buttons or entering codes on MTMKB keypads. You can open the door or activate the AUX relay from your phone, via the numeric keypad while communicating or via the dial-to-open function.

It supports configuration and management via the CONNECT SetUp app and is compatible with CAME Key.

Connect and control up to 2 CAME operators and use its gateway function. It supports sending commands to entry panels and operators via the Automation app.

FEATURES

- Manages up to 3000 telephone numbers
- 2 call buttons
- 2 on-board controls: electric lock and auxiliary control (1A, 30V max)
- LED pictograms for status alerts: door opening, active communication, call in progress and system busy
- Adjustable speaker, microphone and electric lock
- Dual blue or white backlit name tags with brightness settings
- Water and dust protection rating IP54
- Configuration and management via the CONNECT SetUp app
- MiniUSB front panel for firmware updating and programming.

DIMENSIONS

