MTM VR ZAMAK & AGT

ENTRY PANEL

RECEIVER



Surface kit shown - includes rainshield

CONTENTS


- Audio module for System 200
- Front piece for module with one to ten buttons
- Frame with one- or two-module profile
- System 200 control module and power supply
- Audio receiver with handset
- Maximum cable distance 250m

See page 168


IP54 IK09 CABLE P168 DIAGRAM

KITS

Buttons/Way	Mounting	Modules	Kit Code	
1 WAY	Flush	1	MTMFVRAGA1	
	Surface		**MTMSVRAGA1**	
2 WAY	Flush		MTMFVRAGA2D	
	Surface		**MTMSVRAGA2D**	
3 WAY	Flush	2	MTMFVRAGA3	
	Surface		**MTMSVRAGA3**	
4 WAY	Flush		MTMFVRAGA4	
	Surface		**MTMSVRAGA4**	
5 WAY	Flush		MTMFVRAGA5	
	Surface		**MTMSVRAGA5**	
6 WAY	Flush		MTMFVRAGA6D	
	Surface		**MTMSVRAGA6D**	
7 WAY	Flush		MTMFVRAGA7D	
	Surface		**MTMSVRAGA7D**	
8 WAY	Flush		MTMFVRAGA8D	
	Surface		**MTMSVRAGA8D**	
9 WAY	Flush		MTMFVRAGA9D	
	Surface		**MTMSVRAGA9D**	
10 WAY	Flush		MTMFVRAGA10D	
	Surface		**MTMSVRAGA10D**	



FLUSH KITS
Include back box.




SURFACE KITS
Include rainshield.

Item	Description	Code	
AGT	Intercom handset	**AGT A 200K (840CA-0030)**	







MTM VR

THE RANGE OF EXTERNAL MODULAR ENTRY PANELS

COMPATIBLE SYSTEMS



DIGITAL DIALING

The digital display allows a phone book with up to 7200 names to be displayed. During the programming phase you can choose the most appropriate search mode based on the number of users, a scrolling list or an alphabetical block search.

BUTTON COMPOSITION

On the call module, you can customise the amount of buttons required. Using a variety of modular front plates you can achieve maximum button composition flexibility. Available with 2, 3, 4 and 8 button front plates.


ACCESS CONTROL

The MTM range also includes 2 modules specifically for access control, one that is keypad operated and the other RDIF reader operated. Both modules are fitted with 2 on-board relay switches and 2 inputs for directly activating the relay switches.

A key feature of MTM VR is the durability and strength of the materials. The modular entry panel does not go unnoticed. It uses the same electronic modules and easy to fit functionality as the standard MTM however, it uses an IK09 rated vandal resistant Zamak composite with crush proof buttons and anti-tamper screws.

IK09


VISUAL ANGLE



FEATURES

- Zamak finish
- Direct connection to an analogue camera (X1 audio)
- High efficiency illuminator with anti-glare diffuser
- Sound and visual alerts
- HD resolution and High Dynamic Range (HDR) technology
- Blue or white backlit tag holders with brightness settings
- MiniUSB front panel for firmware updating and programming
- Up to 98 button calls and unlimited digital calls

DIMENSIONS



CAME

AGT A

HANDSET INTERCOM WITH SOFT-TOUCH BUTTONS, 1 PROGRAMMABLE AUX BUTTON, WHITE.

COMPATIBLE SYSTEMS



TECHNICAL DATA

Dimensions (mm)	116 x 190 x 44.5
Power supply by BUS (V)	15 ÷ 20 DC
Absorption by BUS (mA)	30
Consumption in stand-by mode (mA)	<0,5
Operating temperature (°C)	+5 ÷ +40
Protection rating (IP)	30
Colour	White

Wall-mounted intercom with 3 main soft-touch buttons for door opening, programmable auxiliary control and ringtone adjustment/ exclusion (with signaling LED when excluded). It allows manging the “gate opener” function and displays the status of the gate controlled by means of a signaling LED. Prearranged for wall installation on horizontal and vertical 503 box and on round Ø 60 mm box.

FEATURES

- Handset with magnetic hang-up
- Concealed LED signal
- AUX2 for auxiliary functions and call to the porter
- Automatic door-opener function
- Door-opener soft-touch button
- Programmable auxiliary soft-touch button
- Soft-touch button for ringtone adjustment/ exclusion with LED indicator when excluded
- Latch function (gate opener) for checking the status of external automations

DIMENSIONS



ACCESSORIES



AGT KTA

Desktop stand. Plexiglass 10mm thick stand supplied with white RJ45 cable and terminal board cover with PMMA laminate - metallic grey

CAME