MTM STANDARD & XTS 7

ENTRY PANEL WITH KEYPAD & DIGITAL DISPLAY RECEIVER

WiFi COMPATIBLE



Surface kit shown - includes rainshield
Phone not included.
Shown for illustrative purposes only.

CONTENTS


- Audio-video module for X1 System
- Front piece for module with keypad and digital display
- Frame with three module profile
- X1 control module and power supply
- Video receiver with 7” colour LCD display
- Video call via app to 4 iOS or Android devices
- Maximum cable distance 100m

IP54 IK07 CABLE P170 DIAGRAM


KITS

Buttons/Way	Mounting	Modules	Kit Code ● Receiver	Kit Code ○ Receiver	
1 WAY	Flush	3	MTMFKDX7B1	MTMFKDX7W1	
	Surface		**MTMSKDX7B1**	**MTMSKDX7W1**	
2 WAY	Flush		MTMFKDX7B2	MTMFKDX7W2	
	Surface		**MTMSKDX7B2**	**MTMSKDX7W2**	
3 WAY	Flush		MTMFKDX7B3	MTMFKDX7W3	
	Surface		**MTMSKDX7B3**	**MTMSKDX7W3**	
4 WAY	Flush		MTMFKDX7B4	MTMFKDX7W4	
	Surface		**MTMSKDX7B4**	**MTMSKDX7W4**	
5 WAY	Flush		MTMFKDX7B5	MTMFKDX7W5	
	Surface		**MTMSKDX7B5**	**MTMSKDX7W5**	
6 WAY	Flush		MTMFKDX7B6	MTMFKDX7W6	
	Surface		**MTMSKDX7B6**	**MTMSKDX7W6**	
7 WAY	Flush		MTMFKDX7B7	MTMFKDX7W7	
	Surface		**MTMSKDX7B7**	**MTMSKDX7W7**	
8 WAY	Flush		MTMFKDX7B8	MTMFKDX7W8	
	Surface		**MTMSKDX7B8**	**MTMSKDX7W8**	
9 WAY	Flush		MTMFKDX7B9	MTMFKDX7W9	
	Surface		**MTMSKDX7B9**	**MTMSKDX7W9**	
10 WAY	Flush		MTMFKDX7B10	MTMFKDX7W10	
	Surface		**MTMSKDX7B10**	**MTMSKDX7W10**	

Item	Description	Code ● Receiver	Code ○ Receiver	
XTS 7 B/W	Full touch video intercom	**XTS/7X2 BK WIFI**	**XTS/7X2 WH WIFI**	



FLUSH KITS
Include back box.





SURFACE KITS
Include rainshield.



COLOURS
Available in black and white







MTM

THE RANGE OF EXTERNAL MODULAR ENTRY PANELS

COMPATIBLE SYSTEMS







DIGITAL DIALING

The digital display allows a phone book with up to 7200 names to be displayed. During the programming phase you can choose the most appropriate search mode based on the number of users, a scrolling list or an alphabetical block search.

BUTTON COMPOSITION

On the call module, you can customise the amount of buttons required. Using a variety of modular front plates you can achieve maximum button composition flexibility. Available with 2, 3, 4 and 8 button front plates.

ACCESS CONTROL

The MTM range also includes 2 modules specifically for access control, one that is keypad operated and the other RDIF reader operated. Both modules are fitted with 2 on-board relay switches and 2 inputs for directly activating the relay switches.


MTM has an extensive range of modular configurations, that are compatible with five different systems, allowing multiple functions to be carried out.

It's clean design has strong aesthetic appeal in all installation scenarios, while maintaining simple functionality.

Particular attention to detail has been paid to the finish, by eliminating the speaker holes, backlighting the keypad to give
it a sleek look, and using satin aluminium for durability.

IK07


VISUAL ANGLE



FEATURES

- Anodised and frosted natural aluminum finish
- Unique design without typical speaker holes
- Direct connection of an analogue camera (audio X1)
- High efficiency illuminator with anti-dazzle diffuser
- Acoustic and visual signals
- HD resolution (IP Camera version only) and HDR technology (High Dynamic Range)
- Backlighting of blue or white label holders with intensity adjustment
- Front mini USB for firmware updates and programming
- Up to 98 call buttons and unlimited digital calls

DIMENSIONS



CAME

XTS 7 X2

HANDSFREE 7" VIDEO ENTRY SYSTEM FOR X1 AND XIP SYSTEMS

COMPATIBLE SYSTEMS



TECHNICAL DATA


Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Colour	Black / White

Surface mounted monitor with 7″ TFT touch-screen display with Optical Bonding technology, integrated WiFi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. Local power supply 14 - 18 V DC. On-board web server for configuring and updating firmware. It includes bracket for surface mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with corresponding box. Compatible with the X1 and XIP systems.

FEATURES

- Half-duplex audio speakerphone
- 7″ TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 V DC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- “Panic” function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different ringtones for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

DIMENSIONS



CAME