VRM & AGT

ENTRY PANEL RECEIVER



Surface kit shown - includes rainshield

CONTENTS

- Audio module for System 200
- One piece faceplate with one to ten buttons
- Frame with one- or two-module profile
- System 200 control module and power supply
- Audio receiver with handset
- Maximum cable distance 250m

See page 168

IP54 IK09 CABLE P168 DIAGRAM


KITS

Buttons/Way	Mounting	Modules	Kit Code	
1 WAY	Flush	2	VRMFAGA1	
	Surface		**VRMSAGA1**	
2 WAY	Flush		VRMFAGA2	
	Surface		**VRMSAGA2**	
3 WAY	Flush		VRMFAGA3	
	Surface		**VRMSAGA3**	
4 WAY	Flush		VRMFAGA4	
	Surface		**VRMSAGA4**	
5 WAY	Flush		VRMFAGA5	
	Surface		**VRMSAGA5**	
6 WAY	Flush		VRMFAGA6	
	Surface		**VRMSAGA6**	
7 WAY	Flush	3	VRMFAGA7	
	Surface		**VRMSAGA7**	
8 WAY	Flush		VRMFAGA8	
	Surface		**VRMSAGA8**	
9 WAY	Flush		VRMFAGA9	
	Surface		**VRMSAGA9**	
10 WAY	Flush		VRMFAGA10	
	Surface		**VRMSAGA10**	


Item	Description	Code	
AGT	Intercom handset	**AGT A 200K (840CA-0030)**	

LASER ENGRAVING
Customised laser engraving requires up to 5 days lead time (maximum).






SURFACE KITS
Include rainshield.



FLUSH KITS
Include back box.







VRM

FLAT PLATE WITH UK MANUFACTURED BUTTONS

COMPATIBLE SYSTEMS

X1 · XiP · IP360 · GSM · 200







DIGITAL DIALING

The digital display allows a phone book with up to 7200 names to be displayed. During the programming phase you can choose the most appropriate search mode based on the number of users, a scrolling list or an alphabetical block search.

PUSH BUTTON COMPOSITION

On the call module, you can customise the amount of buttons required. Using UK manufactured push buttons, you can achieve maximum button composition flexibility.

ACCESS CONTROL


The VRM range can accommodate the MTM VR keypad unit for standalone access control as well as the unique 'Universal reader bracket' able to house most types of common proximity access control reader.

A key feature of VRM is the durability and strength of the materials. It uses the same electronic modules and easy to fit functionality as the standard MTM however, it uses an IK09 rated vandal resistant marine grade stainless steel manufactured in the UK.

Vandal resistant entry panels are available in a number of finishes such as Stainless Steel, Highly Polished Steel, Brass and can be custom powder coated in any RAL colour of your choice.

IK09

VISUAL ANGLE




FEATURES

The benefits of MTM VR plus:

- Bespoke finishes
- Laser engraving
- Unmatched video quality
- IP65 rated bespoke buttons
- Manufactured in the UK
- Impact & water resistant
- Custom sizes

DIMENSIONS



AGT A

HANDSET INTERCOM WITH SOFT-TOUCH BUTTONS, 1 PROGRAMMABLE AUX BUTTON, WHITE.

COMPATIBLE SYSTEMS



TECHNICAL DATA

Dimensions (mm)	116 x 190 x 44.5
Power supply by BUS (V)	15 ÷ 20 DC
Absorption by BUS (mA)	30
Consumption in stand-by mode (mA)	<0,5
Operating temperature (°C)	+5 ÷ +40
Protection rating (IP)	30
Colour	White

Wall-mounted intercom with 3 main soft-touch buttons for door opening, programmable auxiliary control and ringtone adjustment/ exclusion (with signaling LED when excluded). It allows manging the “gate opener” function and displays the status of the gate controlled by means of a signaling LED. Prearranged for wall installation on horizontal and vertical 503 box and on round Ø 60 mm box.

FEATURES

- Handset with magnetic hang-up
- Concealed LED signal
- AUX2 for auxiliary functions and call to the porter
- Automatic door-opener function
- Door-opener soft-touch button
- Programmable auxiliary soft-touch button
- Soft-touch button for ringtone adjustment/ exclusion with LED indicator when excluded
- Latch function (gate opener) for checking the status of external automations

DIMENSIONS



ACCESSORIES



AGT KTA

Desktop stand. Plexiglass 10mm thick stand supplied with white RJ45 cable and terminal board cover with PMMA laminate - metallic grey

CAME