ED5



Overview

The ED5 Handset allows an occupant of a dwelling to answer a call from a visitor at a communal entrance and have a two-way simultaneous conversation. They can then enable the remote operation of the electric locking device to permit the visitor access.

The ED5 is constructed from hard wearing HIPS plastic in a sleek and modern design. HIPS has good mechanical properties; impact resistance and toughness. The handset is a 'surface mount' design for easy installation.

The ED5 is compatible with APEX, Elite and legacy DC systems.

- Handset with cradle switch hangup
- Door Status LED
- Privacy Status LED
- External call tone adjustment via slider switch
- Timed Privacy function, 6 timeout settings, 5,15 or 30 minutes, 1,4 or 8 hours. Can be disabled or latched on/off
- Buttons: 16mm door release, privacy and concierge call back buttons
- Laser Engraved cover

ACCESSORIES

AGT K TA



Desktop stand. Plexiglass 10mm thick stand supplied with terminal board cover with PMMA laminate - metallic grey

116mm





Technical characteristics

MODEL ED5 (840CA-0070) **Buttons** 16mm door release, privacy and concierge call back buttons Privacy 6 timeout settings, 5,15 or 30 minutes, 1,4 or 8 hours. Can be disabled or latched on/off Pulsed tone with External volume adjustment slider on RHS. Muted call tone when on privacy Call tone Operating Voltage 12-15V DC (13.8V Nominal) **Power Consumption** 2.6W Max, 0.15W Quiescent Cabling CAT5/ CW1308 4 pair minimum (leaves 1x core spare) - Note: 3 pair can be used if Door Open LED function omitted Connections 10-way Screw Terminal - slotted head 115 x 189 x 27 (without receiver) 115 x 189 x 50mm (with receiver) (approximate excluding cable) Dimensions White Colour