

46004 MULLION READER

FOR INTERNAL AND EXTERNAL USE



Features


Surface mounted mullion reader for internal and external use. Designed to be mounted directly onto a wall, pedestal or other flat surface, compatible with metallic surfaces i.e stainless steel, lift car interiors or gate posts.

- Fully potted construction for robustness
- Protections: short circuit, SIG wire to 0v, SIG wire to 12v
- DC voltage input detection, LED flashes at <9.5v and >14v
- Compatible with:
 - CAME KMS HF Dual
 - CAME KMS LF Sharktooth
 - PAC LF
 - PAXTON fobs
- Low profile, smooth edged design
- Large and clear LED indicator
- Reads 125khz and 153khz frequency tokens
- 5 years warranty

TECHNICAL INFORMATION

RFID Reader Frequency	125 -153 KHz
RFID Read Range	15-30mm – 20mm typical
Data Format	SIG data, 26bit or 32bit Weigand
LED	Blue: door locked (static), low voltage (flashing) Red: Access denied Green: fob detected (momentary), Access Authorised (timed - system controlled)
Sounder	Piezo Buzzer, 85dBA, Selectable On/Off
Operating Voltage	10.5-14.5VDC (13.8V Nominal)
Power	1.44W Idle, 2.28W Active
Protection	Short circuit, reversed polarity, SIG to 0v, SIG to 0v
Connections	Pigtail 500mm; Cable Assembly: 12V, 0V, SIG, Weigand D0, Weigand D1, Weigand Format selector, LED, Sounder
Material	PC/ABS
Rating	IP55

DIMENSIONS



CAME KMS

A2 Glory Park, Glory Park Avenue, Wooburn Green HP10 0DF
Tel: 01494 531099 Email: ckuk.info@came.com

CAME KMS